

Double Sided Mastic Tape

Product Description

- Synthetic rubber based extruded bonding and sealing strip
- Medium to hard composition
- Carefully selected fillers to provide good stability at higher temperatures

Applications

- Lap joining of plastic sheeting such as DPCs and DPMs
- Sealing of panels in water storage tanks
- Higher specification roofing applications such as rooflight manufacture
- Sealing of caravan rails such as awning and gutter details

Technical Performance

Description	Units	Value	Test Method
Specific Gravity	g/cm ³	1.5	In House
Shear Adhesion	N/cm ²	22	In House
180° Peel Adhesion (1mm thick)	N/cm	24	In House
Force to compress by 20%	N/cm ²	7	In House

Performance Characteristics

Application Temperature	>4°C
Service Temperature	-40°C to +90°C
UV Resistance	Good
Chemical Resistance	Good to dilute acids and alkalis

Surfaces should be clean, dry and free from oil or grease

Features and Benefits

- Easy and accurate to use with little waste and no mess
- Can be supplied in roll form or ready-cut pads
- Approvals include WRC (portable water contact) for black version
- Black or white are standard colours. Others subject to minimum order quantity.

Storage Details

- Shelf Life is 2 years at 5 -25°C in dry conditions (in original packaging)



Accredited

Reprocessor
DOE ER199846

Valpak

2001 Challenge
Award Winner
Recycling